


ERRATA for
PE Civil: Structural Practice Exam
 ISBN: 978-1-947801-31-8
 Copyright 2023
 Errata posted 01/06/2025

Revisions are shown in red.

Question 11, p. 11:



- A. 1.96
- B. 2.13
- C. 21.7
- D. 24.8

Question 31, p. 23:

An A992 W8×28 beam is loaded as shown. To have zero deflection at the free end of the overhanging section, the magnitude (kips) of the concentrated force, **P**, at the free end must be _____. **Ignore member self-weight.**

Question 36, p. 26:

A contractor is planning to install a temporary structure that will support a concrete pump at a construction site. According to the construction contract, the contractor must submit design drawings and calculations for the temporary structure to the **project engineer of record** for approval. What is the purpose of this submittal requirement?

ERRATA for
PE Civil: Structural Practice Exam
ISBN: 978-1-947801-31-8
Copyright 2023
Errata posted 01/06/2025

Question 37, p. 27:

According to IBC 2018 and applicable quality assurance inspection requirements, which of the following inspection tasks are required for ASTM A325 high-strength bolts in a snug-tightened joint used in a steel-framed structure?

Question 51, p. 36:

Per ASCE 7-16, the estimated design lateral soil load (psf/foot of depth) for nonrigid walls is most nearly:

Question 57, p. 40:

Using ACI 318-14's simplified method of analysis, the maximum factored negative moment in the slab (ft-kips/ft) is most nearly:

- C. 1.62

Question 65, p. 48:

Option B should read as follows:


- B. ASD = 21.3
LRFD = 32.1

Question 74, p. 52:


For the figure shown, unfactored vertical reactions from the grade beam to the drilled pier are LL = 10 kips and DL = 8 kips. According to ASCE 7-16, the minimum horizontal design strength (lb) of the connection from the grade beam to the drilled pier is most nearly:

ERRATA for
PE Civil: Structural Practice Exam
ISBN: 978-1-947801-31-8
Copyright 2023
Errata posted 01/06/2025

Question 79, p. 54:



Question 80, p. 55:



ERRATA for
PE Civil: Structural Practice Exam
ISBN: 978-1-947801-31-8
Copyright 2023
Errata posted 01/06/2025

Solution 11, p. 60:

$$R_a (24 \text{ ft}) - 0.640 \text{ kips}(24 \text{ ft}) - 2 \text{ klf} (24 \text{ ft})^2 / 2 + 20 \text{ ft-kips} + 1.55 \text{ klf} (8)^2 / 2 + 0.1 \text{ kips}(8 \text{ ft})$$

$$R_a (24 \text{ ft}) - 15.36 \text{ ft-kips} - 576 \text{ ft-kips} + 20 \text{ ft-kips} + 49.6 \text{ ft-kips} + 0.8 \text{ ft-kips}$$

$$R_a = \frac{-520.96 \text{ ft-kips}}{24 \text{ ft}} = -21.7 \text{ kips}$$

Solution 57, p. 78:

$$l_n = 10 \text{ ft} - 1 \text{ ft} = 9 \text{ ft per Sec. 6.5}$$

$$W_u = 1.2 \times 100 + 1.6 \times 50 = 200 \text{ plf}$$

Use $W_u l_n^2 / 10$ (max of all applicable support conditions)

Note: Beam/column stiffness not applicable to slabs

$$M_u = W_u l_n^2 / 10 = 1.62 \text{ ft-kips/ft}$$

THE CORRECT ANSWER IS: C


Solution 61, p. 79:

By inspection P controls. P is limited by the yielding of the horizontal leg of the angle. Use plate yielding limit state, per section F11.1.

ERRATA for
PE Civil: Structural Practice Exam
 ISBN: 978-1-947801-31-8
 Copyright 2023
 Errata posted 01/06/2025


Solution 62, p. 80:

- WOOD
- DIAPHRAGM DEFLECTION CAN BE TOLERATED




Flexible
 Torsionally **regular**

- METAL DECK SUPPORTED BY STEEL BEAMS AND COLUMNS



Flexible
 Torsionally regular


- PT CONCRETE SLAB SUPPORTED BY CONCRETE COLUMNS/BEAMS



Rigid
 Torsionally regular

- CONCRETE SLAB SUPPORTED BY MASONRY WALLS

$$A_{\text{STORYDRIFT}} = 1.5 \left(\frac{A_{\text{STORYDRIFT}} + B_{\text{STORYDRIFT}}}{2} \right)$$



Torsionally irregular
 Rigid

ERRATA for
PE Civil: Structural Practice Exam
ISBN: 978-1-947801-31-8
Copyright 2023
Errata posted 01/06/2025

Solution 65, p. 81:

Reference: AISC, 15th ed.

$$R_n = F_n A_b$$

$$\phi = 0.75, \Omega = 2.00$$

Equation J3-1

ASD:

$$F_{nv} = 27 \text{ ksi}$$

$$F_{nv}/\Omega = 13.5 \text{ ksi}$$

Table J3.2

$$\text{Allowable load} = 2(13.5)(0.79) = 21.33 \text{ kips}$$

LRFD:

$$\phi R_n = \phi F_{nv} A_b$$

$$\phi F_{nv} = 20.3 \text{ ksi (A307 bolts)}$$

$$\phi R_n = (20.3)(0.79)(2) = 32.07 \text{ kips}$$

Alternate solution, use Table 7-1

Solution 74, p. 86:

Reference: ASCE 7-16, Section 12.1.4, p. 89 and Section 1.4.3, p. 4

Unfactored reactions from grade beam to drilled pier:

$$\text{LL} = 10 \text{ kips}$$

$$\text{DL} = 8 \text{ kips}$$

Solution 75, p. 86:

J 3.5 max edge distance $12(t) = 12(3/4) = 9 \text{ in.}$, 6 in. maximum governs.

THE CORRECT ANSWERS ARE: A, D, F

Solution 79, p. 88:

$$P_h = \frac{K_a \gamma z^2}{2}$$

$$= \frac{0.40586(125 \text{ psf})(8 \text{ ft})^2}{2}$$

$$= 1,623 \text{ lb/ft}$$